ZKSoftware
The Advanced Biometric Solution



SC102/3

ZKSoftware RFID Access Control The Bright Star of Security



SC202/3



SC302/3



SC402/3

ZKSoftware Inc. reserved the copyright of this page, if any change occured, ZKSoftware is not responsible to notice in advance.

ZKSoftware
The Advanced Biometric Solution



SC102/3



SC202/3

Technical Specifications - SC102/202/302/402

- **Card Holders:** 10000 cards
- **Transaction Capacity:** 30000 records
- **CPU:** 64bit ZK6001 Microprocessor
- **Hardware:** ZEM500(Embedded Linux O/S)
- **Access Mode:** Card Only, PIN Only, Card+PIN
- **Read Range:** 10-15 cm
- **I/O Interface:** RS232(10m)/485(1.2km)
- **Baud Rate:** 9600-115Kbps programmable
- **Ethernet:** 10/100M
- **Wiegand Output any bit**
- **USB:** Mini-USB 2.0 port
- **Access Control Function:** 50time zones, 5groups,10open door combination, supports multi-users enter. TTL for connecting to lock, door sensor, exit button, alarm
- **LCD Panel:** 4 line,16 character each line(User name, ID number, time, date, states)
- **Keypad:** 4x4 metal keypad with 4 function keys
- **Audio Visual Indicator:** Red LED(Access denied)/ Green LED(Access granted) with Audible Beep
- **Housing Material:** ABS
- **Power Requirement:** 12V DC, 400mA
- **Operating Temperature:** 0°C-45°C **Operating Humidity:** 20%-80%
- **Options:** Webserver, Wiegand Input, Antipass-back, Multi-language display.



SC302/3



SC402/3

Technical Specifications - SC103/203/303/403

- **Card Holders:** 30000 cards
- **Transaction Capacity:** 50000 records
- **CPU:** 64bit ZK6001 Microprocessor
- **Hardware:** ZEM500(Embedded Linux O/S)
- **Access Mode:** Card Only, PIN Only, Card+PIN
- **Read Range:** 10-15 cm
- **I/O Interface:** RS232(10m)/485(1.2km)
- **Baud Rate:** 9600-115Kbps programmable
- **Ethernet:** 10/100M
- **Wiegand I/O:** any bit
- **USB:** Mini-USB 2.0 port
- **Access Control Function:** 50time zones, 5groups,10open door combination, supports multi-users enter. TTL for connecting to lock, door sensor, exit button, alarm
- **LCD Panel:** 4 line,16 character each line(User name, ID number, time, date, states)
- **Keypad:** 4x4 metal keypad with 4 function keys
- **Audio Visual Indicator:** Red LED(Access denied)/Green LED(Access granted) with Audible Beep
- **Housing Material:** ABS
- **Power Requirement:** 12V DC, 400mA
- **Operating Temperature:** 0°C-45°C **Operating Humidity:** 20%-80%
- **Options:** Webserver, Antipass-back, Multi-language display.

For distributors

ZKSoftware Inc. Http://www.zksoftware.com
ZK Mansion, Wuhe Rd., Gangtou, Bantian, Buji Town, Longgang District, Shenzhen China 518129
Tel: 86-755-8960 2345/46/47/48 Fax: 86-755-8960 2675
No. 2007-09